

# Viking Peel & Stick Tanking Membrane

Version: VPS-PTS-V1

## Product description

Viking Peel & Stick Membrane is a self-adhering, damp-proof membrane (DPM) waterproofing system for vertical and horizontal tanking applications. It is primarily adhered to the outside of a sub-structure of a building (such as a foundation or basement) to prevent water ingress. Other forms of tanking where Peel & Stick can be used include under floor slabs, behind masonry walls, the lining of substrates of in situ or pre-cast concrete; retaining walls, cellars, lift shafts, tunnels, plaza decks, roof gardens and planter boxes.

Peel & Stick consists of a 1.5mm thick rubberised asphalt membrane, on the face of which a heavy-duty, high impact polyethylene film is laminated. It is easy to install (aiding a quality finish), with the adhesive side having a removable release sheet which is peeled back at the time of application to the substrate. It is cold-applied, so it is useful in restricted areas where the use of a flame is not an option. The Peel & stick system consists of the membrane, bituminous primer, liquid mastic sealant, protection boards and drainage boards

Peel & Stick provides full-adhesion to eliminate water migration. Peel & Stick can be adhered to various substrate types and the bond improves over time. It possesses elastomeric properties, so the membrane forgives movement and provides flexibility over cracks. It is mechanically strong and resists hydrostatic pressure. Viking Peel & Stick comes in rolls 1.5mm thick x 0.914m wide (fewer seams) x 20.4m long. The Peel & Stick is BRANZ Appraised No. 826, and comes with a 20-year product warranty. Viking Roofspec is an active member of the Waterproofing Membrane Association Inc. (W.M.A.I.); an incorporation of companies whose goal is to lift the standard of waterproofing in New Zealand. The W.M.A.I. is formulating a "Tanking Code of Practice" for the Department of Building and Housing.

## Purpose and use

Viking Peel & Stick Membrane has been appraised for use:

- On buildings subject to non-specific design under floor slabs complying with NZS 3604 and behind concrete masonry basement walls and under floor slabs complying with NZS 4229; and,
- on buildings subject to specific design with substrates of insitu or precast concrete complying with NZS 3101 or concrete masonry complying with NZS 4230; and, 4210
- where subsoil drainage and free draining granular backfill has been placed behind basement walls.
- Viking Peel & Stick tanking membrane must be adequately protected against damage during backfilling and in service.
- The product must be installed by Viking Roofspec approved installers.

## Conditions

- The product can be used on substrates of plywood, concrete, PIR Polyiso Insulation, or SIP's, subject to specific structural and weathertightness design.
- The weathertightness design of junctions for each specific structure is the responsibility of the building designer.
- The product will assist with meeting the provisions of the New Zealand Building Code clauses B1 and B2, provided it is employed in accordance with the supplier's installation and maintenance requirements.
- The product is suitable for use in all Climate Zones as defined in NZBC H1/AS1 and all Exposure Zones as defined in NZS3604.

## Compliance with the New Zealand Building Code

This system will, if employed in accordance with the supplier's installation and maintenance requirements, assist with meeting the following provisions of the building code:

- Clause B2 Durability: Performance B2.3.1, B2.3.1(a), B2.3.2, B2.3.2(a)
- Clause E2 External moisture: Performance E2.3.3
- Clause F2 Hazardous building materials: Performance F2.3.1

July 2023

## PRODUCT TECHNICAL STATEMENT



### Design Requirements

Product specification and incorporation of Viking Peel & Stick Tanking Membranes into the building design shall be carried out by a designer/architect/engineer or a building professional who:

- Is qualified to design the buildings covered under the 'Scope' of use of this product.
- Has ready access to the technical specifications including installation details and standards referenced in the BRANZ Appraisal No. 864 where the design limitations are outlined for the scope of this PTS.
- Accessories in the Peel & Stick Tanking Membrane system include bituminous primer (20L), bituminous gum, protection boards and drainage boards.

### Installation Requirements

Installation of the Viking supplied system shall be carried out by a Viking Roofspec trained and licensed installer. Installation shall be undertaken in accordance with all relevant technical information related to the selected installation method, including information contained within the current Viking PDS and Viking Installation Guide

### Quality assurance

- BRANZ Appraisal No. 826
- Masterspec 4131VP: Viking Peel & Stick Tanking Membrane
- Tanking Code of Practice
- Viking Peel & Stick Tanking Membrane PTS
- Viking Peel & Stick Tanking Membrane PDS
- Viking Peel & Stick Tanking Membrane Detail

### Warranty information

Viking Peel & Stick Tanking Membranes are backed by Vikings 20-year product warranty with Certificate of Workmanship provided by Viking Approved Applicator companies. Viking Roofspec only supply Viking Mercury FC Membrane systems to our Approved Applicator network of Viking Licensed Installers.

#### **Auckland office**

80 Alexander Crescent,  
Otara PO Box 14-541,  
Panmure, Auckland  
1741, New Zealand

#### **Christchurch office**

2 Nazareth Avenue,  
Middleton, PO Box  
9117, Tower Junction  
Christchurch 8149,  
New Zealand

#### **Wellington office**

19 Pretoria St,  
Lower Hutt 5010,  
New Zealand

T: 0800 729 799

F: 0800 729 788

[info@vikingroofspec.co.nz](mailto:info@vikingroofspec.co.nz)

[www.vikingroofspec.co.nz](http://www.vikingroofspec.co.nz)

A division of Viking Group Limited